


技術要求  
Specification

1. 插頭、電線、尾插通過IMQ認證合格。  
Plug: According to standard IEC884; VDE Approval.  
Connector: According to standard IEC 320 C7; VDE Approval.  
Flexible Cord: According to standard IEC 227; Approval: VDE.
2. 插頭耐高壓2000V/1min.尾插耐高壓4000V/1min.而不發生異常。  
Plug withstand 2000v/1min.Connector withstand 4000v/1min. No flashover and no damage.
3. 訂線長度為1500mm.  
Length: 1500mm.
4. 尾部處理:LT-207.  
End Treatment: LT-207
5. 繞線包裝方式:一般。  
Hanking & packing: As usual.
6. 注意事項:所有原物料均符合ROHS標準。  
Note: All material must comply with ROHS.



6	內模 Inner body	503無極內模(P/N: YM-B8-60)	Y.M	BK	1
5	尾插 Connector	LT-503, PVC: 50P	H.G	BK	
4	端子 Terminal	Ø2.35花瓶端	J.H	YL	2
3	主體 Body	LT-207, PVC:50P	H.G	BK.	
2	腳架 Insert	Ø4.0腳架(P/N: DC-0002A-17)	D.C	BK	2
1	電線 Cord	H05VVH2-F 0.75/2C	T.Y	BK	1
序號 NO.	名稱 item	材料規格 specification	供應商 supplier	顏色 colour	數量 q'ty

A	繪圖 drawing	魏芝佳	日期 Date	09.07.29	型號 Cat.NO.	LT-207+503
	審核 review	<i>[Signature]</i>	比例 Scale	1:1	客戶 Customer	武進紅光
版次 revision	核准 approval	<i>[Signature]</i>			客戶料號 P/N.	NA
	單位 unit	mm			聯盛品號 LS no.	NA

LEADERSHIP ELECTRIC COMPONENT CO.,LTD.